



Freely programmable, multifunctional display

Linux HMI VC is a 5" full-colour display with a powerful ARM CPU. The open software platform has a choice of tools for design of premium graphical user interfaces. This, together with WVGA display resolution and high brightness display, enables fast design of sharp interfaces with high usability.

With touch screen and configurable soft keys, operators are offered a user friendly interaction with the system. Linux HMI VC has multifunctional capability and can be used as instrumentation display, control system GUI, video monitor, Service tool and more.

Features

PART NUMBER	8 PROGRAMMABLE SOFT KEYS	TOUCH SCREEN	BONDED SCREEN FOR HIGHEST READABILITY
135-02	•		
135-06	•	•	
135-07	•		•

Faria Beede Instruments, Inc.
P. O. Box 983
Uncasville, CT 06382
860.848.9271
Fax: 860.848.2704

88 Village Street
Penacook, NH 03303
603.753.6362
Toll-free: 800.451.8255
Fax: 603.753.6201



Made in the USA

fm-001-0111 rev A 02/2015

Built for :  **Linux**

www.FariaBeede.com

Specifications

KERNEL

MAIN PROCESSOR	Freescale i.MX 537, 32 Bit ARM processor. Runs freely programmable Linux system and LinX Software Suite base package.
CO-PROCESSOR	Runs watchdog functions controlling integrity of product, for increased reliability and safety.
STORAGE	512 MB Flash
RAM	256 MB DDR3

DISPLAY

TYPE	TFT with LED backlight and anti-glare coated glass
SIZE AND RESOLUTION	5" WVGA, 800 x 480 pixels
COLOR DEPTH	24 bit
BRIGHTNESS	650 Cd/m ²
DIMMING	Automatic dimming through ambient light sensor. Dimming can be controlled manually via soft keys and/or touch screen
OPTICAL BONDING	TFT and glass optically bonded. Optical bonding is optional.

HMI

TOUCH SCREEN	Type: Resistive. Touch screen is optional.
SOFT KEYS	8 soft keys, configurable. Soft keys can be used as function keys for the GUI, to control Power On/Off, to control display brightness etc. Soft keys are optional.
BUZZER	For alarms and notifications

INTERFACES

CAN	2 x CAN. ISO11898 2.0B, bitrate configurable 20 – 250 kbps.
ETHERNET	1 x Ethernet. 10/100 Base-T.
USB	2 x USB 2.0. 1 in Deutsch connector and 1 mini-USB under cover on rear side for software upgrading.
VIDEO	1 x Analog Video input. NTSC or PAL.
KEY SWITCH	1 x Key switch input, for start-up/shut down
INPUTS	2 configurable inputs for analog/digital sensors. May be used for measuring resistance/4-20mA/frequency/digital/analog signals.
OUTPUTS	2 configurable high side outputs for driving up to 1A. May be used for continuous driver or PWM output.
POWER SUPPLY	12 or 24 VDC nominal voltage

SOFTWARE

OPERATING SYSTEM	Linux
SOFTWARE APPLICATION PLATFORM	LinX Software Suite, basic package. Extension modules available, eg. CoDeSys.

ENVIRONMENT

IP CLASS	IP66
EMC CONFORMITY	2004/108/EC, ISO 14982:2009
VIBRATIONS	0,02g2/Hz 5-500 Hz
SHOCK	30g/11ms 3x ±10 bumps
TEMPERATURE RANGE (°C)	Operating range -40 to +70 C Storage range -40 to +85 C

ENCLOSURE

HOUSING MATERIAL	Plastic
MECHANICAL INSTALLATION	Flush/panel mounting or mounting on stand/arm with diamond plate.
CONNECTORS	2 x Deutsch DTM 12-pin connectors 1 x Micro/Mini USB -USB 2.0 OTG

SIZE AND WEIGHT

W X H X D (MM)	187 x 112 x 48
WEIGHT (KG)	0.425

