



# Outboard Tachometer Applications

# ISO086

Rev. U ecn 10390 6/2016

Make / Year	Model	# of Poles
<b>Chrysler</b> 1968 - 1983	35 HP, 70 HP & up	12
	55, 60, 85 & 125 HP	20
<b>Force</b> 1984 - 1999	50 HP through early 1987 (A,B models)	8
	35 HP (1986 & later)	12
	40 HP (1991 & later)	
	50 HP (1992 B models & later)	
	70 HP (1991 & later)	
Some older Force engines are 20 pole (see note f.)	90 - 120 HP L-Drive (1991 B & later) 145 HP L-Drive (1991 & later)	
<b>Honda</b> to Present	BF 75/100A, BF 8A, BF 9.9/15A HP	4
	BF 25/30, BF60, BF 75/90 HP	
	BF 40/50 (2006 and later)	6
	BF 115 /130 HP	
Older tiller models require Honda jumper wire 32197-ZH8-003, BF 40/50 HP require 06383-ZV5-315 Tach Kit (thru 2005)	BF 135/150 HP, BF 200/225 HP BF 35/45, BF 40/50 HP (thru 2005) BF 8D/9.9D, BF 15D/ 20D (Includes Power Thrust Models)	12
<b>Mercury/Mariner</b> 1977 to Present (See note "e") *Use Tach adapter #17461A9 Service #17461T9 **Use Tach adapter MM #17461A8 or A10 Service #56-883040A1	18, 25, 48, 60 HP Mariner through 1983	4
	8, 9.9, 15 and 25 HP (4 stroke)(after1998-2004)	
	Less than 40 HP - All Before 1999	12
	40 HP (serial # 582399 and before)	
	8, 9.9 (Before 1999 and after 2005) & 50H (4 stroke)	
	Verado 350 - 400 HP	
	6 to 25 HP 1999 & up, *2002 & up	
SmartCraft requires AGI converter for Analog Gauges.	25 HP & 30 HP (4 stroke) 40 HP (after serial # 582399) 45 HP (1987), 50-60 HP (4 stroke EFI) 50 HP & above, ** 75, 90,115 HP (4 stroke EFI) 135, 150, 200, 225 HP, DI 3.0L EFI 225 & 250 HP Pro Max 3.0L 300 HP EFI	
<b>Evinrude/Johnson</b> 1977 to Present for 88 HP (90) & 112 HP (115) a voltage reg. kit is recommended. A System Check Tach or 2" gauge is required	9.9 HP -15 HP 4 stroke after 2001	6
	All 2 cylinders less than 70 HP ( Pre 1993)	10
	9.9 HP & 15 HP (2 cylinder) (4 stroke)	12
	25-35 HP 3 CYL	
40-50 HP, 2 cylinder (1993 & later)		
60 HP, 3 cylinder (1985 & later)		
	70 HP & greater, including sea drives All FICHT models All E-Tech 40 HP - 250 HP	

Make / Year	Model	# of Poles
<b>Suzuki</b> to Present A System Monitor Tach or 2" gauge is required	Less than 55 HP - All, DT55, 2-Stroke Models 60 HP, 65 HP thru 1985, DT 2-Stroke Models 50 - 60 HP Cabrea, DT 2-Stroke Models	4
	DF 2.5 through DF 15, DF 25 V(TWIN) 2006 & later 25 HP & 30 HP (1993 & later) DT 2-Stroke Models 55 HP & 65 HP (1985 & later) DT 2-Stroke Models	6
	75 HP & up (1985 & later) DF 25 through DF 30 (3 Cyl Models), DT 2-Stroke Models 75 HP and up (Cabrea) DT 2-Stroke Models 115 HP and up (1988 & later), DT 2-Stroke Models DF 40 through DF 250, (4 stroke) ALL	12
	(2 strokes) 8 HP, 9.8, 9.9, 15, 18, 25, 30, 40C, M40C or less (all 2 cylinder) All TLDI 40 through 115	4
<b>Tohatsu / Nissan</b> to Present (See note "e").	(2 strokes) M40D, 40D2, 50D, 50D2, 70B and CM90A (all 3 cylinder)	6
	(4 strokes) MFS20 or less	12
	(2 strokes) 115 HP, 120 HP, 140 HP, M115A-M140A (all 4 cyl.)	
	(4 strokes) 8, 9.8, 9.9, 15, 18, 25 & 30 HP, EFI 25, 30, MFS25/30 (3 cyl)	
<b>Yamaha</b> 1984 to Present	6 HP - 25 HP (2 cyl '84-'87), F/T 9.9 ('85-'91) C25 - C55 (2 cyl) Except C30 (2cyl '93-'97)	4
	S250B and V8 four stroke will not support a conventional tachometer.	6
	F/T 9.9 (MID '92 on), C30-C70 (3 cyl) C30 (2 cyl '93-'97), 25 HP (3 cyl), 25HP (2cyl, '88-'05) C/P/E 30-70, F8, F15, F20	
		F/T 25-F250, HPDI 150-300, 80-SX250 F/T 9.9 (early '92), C75-C150, P75-P200 V / V X 150-250, F15C/F20

### Notes:

a. 6000 RPM tachs are for Inboard & I/O gas engine applications only

b. 7000 RPM & 8000 RPM tachs are for all outboard motor applications only. 20 Pole Tachs are no longer available.

c. Electrical pulses per revolution are equal to 1/2 the number of alternator poles.

d. Older model outboards (prior to 1977) may have the tach signal wire originating at the ignition system though they are alternator equipped. All alternator tachometers may be used on these systems by disconnecting the tach signal wire at the engine and connecting that wire to the unrectified alternator signal at the rectifier. Be certain the number of alternator poles match the tachometer

pole setting of the tach.

e. TOHATSU recommends, when using aftermarket tachs on TLDI engines, using inductor light kit part number 3Y9762510 and Harness 3T5710420. Strong alternator interference on some TOHATSU / NISSAN outboards and some pre 2001 Mercury 90HP outboards may require wiring a .1mf, 100 volt non-polarized capacitor between the signal and ground stud terminals.

f. Faria Beede no longer makes a 20 pole tach.

### 7000 RPM Outboard Tach

OB ALT SWITCH SETTING
1 - 4 POLE
2 - 6 POLE
3 - 8 POLE
4 - 10 POLE
5 - 12 POLE
SLIGHTLY DEPRESS WHILE TURNING

### 6000 RPM w/12 Pole option

ENG. CYL SWITCH SETTING
1 - 4 CYL
2 - 6 CYL
3 - 8 CYL
4 - 12 POLE OB ALT
SLIGHTLY DEPRESS WHILE TURNING